

CARGO VAN CONVERSIONS





CARGO VAN CONVERSIONS

SUPERSTRUCTURE SPECIFICATIONS

- 3mm Mild steel floor
- 3mm Mild steel cross members – spaced 300mm apart with floor gussets
- 1,2mm Smooth bonded Chromadec side panels or 0.8mm Corrugated Aluminium side panels
- Aluminium corner ,roof and bottom extrusions
- Sectional Aluminium roof
- Double rear door with external door lock
- 3 Hinges fitted per door
- Rain gutter fitted above rear doors
- 300mm high kick panels
- 4 Rows wooden slat liners
- 3mm Mild steel light box fitted with standard round truck lights
- Light protectors
- Under run bumper
- Mudflaps
- Reflective tape
- Chevron boards
- Chassis painted in 2K paint



OPTIONAL EXTRAS

- Single side door
- Double side doors
- Fuel saver fairing
- D rubbers
- Tail lift
- Cargo Tracking
- Low profile bull bar





KWAZULU-NATAL

36 Prospecton Road, Prospecton,
Durban, 4133
T +27 31 902 6443

GAUTENG

33 Industry Road, Clayville X4,
Olifantsfontein, 1665
T +27 11 316 4161 • F +27 11 312 4005
www.tfm.co.za

EASTERN CAPE

2 Penkop Street, Woodbrook,
East London, 5200
T +27 43 736 3235